


RESPONSE D30R - NEW: JUNE 2013

This new ProAc model offers a wonderfully natural, musical performance with pinpoint imagery that will appeal to audiophiles and music lovers all over the world

Available in these real wood veneers



Speaker displayed in Ebony Finish.



SPECIFICATIONS



Nominal Impedance

8 ohms

Recommended

Amplifiers

10 to 200 watts

Frequency Response

20Hz to 30KHz

Sensitivity

89 dB linear for 1 watt at
1 metre

Bass Driver

6.5" (165mm) ProAc
unit fitted with carbon
fibre cone with a
polymer rear coating
and concentric damping

Tweeter

D30 (dome): Fitted with
1" silk dome tweeter
with air cooling
D30R (ribbon): ProAc
ribbon unit 60mm by 10
mm as light as a human
hair with rear chamber
damping

Crossover

HQ network using the
finest dedicated
components wired with
multi strand oxygen free
copper cable split for bi
wiring or bi-amplification

Dimensions

Cabinet

Height: 41" (1041mm)

Width: 8.5" (215mm)

Depth: 10.5" (266mm)

Plinth:

Width: 10 1/8" (257mm)

Depth: 12 1/4"

(311mm)

Weight

27 Kgs per cabinet
unpacked

Mode

Floorstanding

Grille

Acoustically transparent
crimlene

Finish

Standard Finishes:

Black Ash, Mahogany,
Cherry, Maple.

Premium Finishes:

