

## BOSTON BRAVO® II



The Boston Bravo II is a compact multipurpose, high performance loudspeaker whose unique design allows it to fit discreetly anywhere in your home especially on walls, in corners, and other tight locations. Sometimes called the on-wall/in-wall, the Bravo II is the perfect choice when you want the speaker to disappear, but can't cut holes in your walls. Its metal grille and contemporary styling also make it the ideal solution for flat panel TV sound.

Your Sound Solution™



**CORNER** / Corner placement is discreet yet ideal for theater, stereo, or whole-house applications. Its unique bracket and 90° corner inserts create a tight, flush fit to any ceiling.



**WALL** / Mounting Bravo II flush to a wall is equally simple when the corner inserts are removed from the bracket.



**CEILING** / Horizontal placement in the wall/ceiling corner offers exceptional, wide-area dispersion, and the ultimate in out-of-the-way placement—perfect for commercial applications too.



**FLOOR** / For a completely hidden system, or a unique surround effect, Bravo II can also be positioned in the corner of a floor and wall.



**BRAVO II CENTER CHANNEL** / When it comes to reproducing critical on-screen dialogue, the magnetically shielded Bravo II Center is right at home on top of your TV. (available in black only)

The Bravo II's quarter-cylinder, wedge-shaped housing contains a 4½-inch woofer and a 1-inch VR® aluminum dome tweeter with AMD™. An adaptable mounting bracket allows it be placed in a wide variety of locations for optimum sound quality and three-dimensional imaging. When a pair is placed vertically in the corners of a room, the Bravo II creates a surprisingly wide sonic window, providing true stereo sound reproduction over a broad area. A unique air channel leading to the exterior vent contributes to the speaker's thin profile while allowing it to breathe openly and provide deep bass response.

To match any décor, the Bravo II is available in black, white, or silver. The Boston Bravo II Center channel is available with MagnaGuard® magnetic video shielding for use with conventional tube televisions.

Unique wedge-shape design allows for placement in corners, ceilings, and other tight locations

Versatile mounting brackets and hardware included

Accurate sound dispersion in both vertical and horizontal positions

Available in black, white or silver with matching metal grille

Aluminum dome tweeter with AMD™ delivers smooth, natural highs

Special center channel is magnetically shielded

Vented enclosure extends low frequencies

Mount Bravo II directly to a single gang electrical block in new construction

**SPECIFICATIONS**

	BRAVO II	BRAVO II CENTER
FREQUENCY RESPONSE (±3dB)	80Hz-20kHz	80Hz-20kHz
RECOMMENDED AMPLIFIER POWER	15-125 watts	15-125 watts
NOMINAL IMPEDANCE	8 ohms	8 ohms
SENSITIVITY [1 watt (2.83v) at 1m]	89dB	89dB
BASS UNIT	4½" (115mm)	4½" (115mm)
TWEETER	1" (25mm) aluminum dome w/AMD™	1" (25mm) aluminum dome w/AMD™
CROSSOVER FREQUENCY	3000Hz	2500Hz
WEIGHT	5 lbs (2.25kg)	5.5 lbs (2.5kg)
DIMENSIONS (HxWxD)	6⅞ x 14⅜ x 4⅜" (167 x 366 x 112mm)	6⅞ x 14⅜ x 4⅜" (167 x 366 x 112mm)
FINISH	Black, white, or silver	Black only