



Technical Information

As with all of our products, the **Cyrus 82 DAC** can be connected to our other systems via our unique **MC-BUS** connectivity.

Inputs – 6 analogue, 2 electrical SPDIF, 2 optical SPDIF, 1 USB (computer slave input)

Sample rate compatibility – digital input: 24-bit/192 kHz; USB: 16-bit/48 kHz

Outputs – Zone 2, preamp out, headphone, bi-wire loudspeakers

Power Supply – 350VA transformer

Power output – 150W per channel into 4 ohms; 70W per channel into 8 ohms

Dimensions (H x W x D) – 73 x 215 x 360 mm

Weight – 6.9kg

Product Overview

Cyrus amplifiers have an enviable reputation for their class leading sound quality corroborated by many international awards from the world's press. Plus you can customise your order from a wide range of options at the point of purchase or by factory upgrade later on.

- The Cyrus integrated amp system is available in two power levels, 2 x 40 or 2 x 70 watts per channel.
- You can order your amplifier with or without a multi-input DAC card.
- Also available for the DAC equipped models is a higher performance up sampling DAC we call the Qx DAC.
- Adding a **PSX-R₂** will enhance the performance of the higher power models.
- A range of superb power amps can be combined with your amplifier for even better sound performance.
- A special preamp only version called **Pre₂ DAC** is designed for those who want to jump into the range using the superior separate power amps.

A modern amplifier should be the focal point of all high performance entertainment systems. Cyrus recognises every customer has a unique requirement for their systems and that these needs often evolve over time as peripheral equipment advances. Therefore customer choice and future flexibility are constructive assets to include in our design thinking.

