

TECHNICAL SPECIFICATIONS:

Power Supply: 110V/60Hz
Power Absorption: 2VA
Speeds: 33 $\frac{1}{3}$ rpm (manual change to 45 rpm)
Speed deviation: $\pm 0.9\%$
Wow and flutter: $\pm 0.15\%$
Rumble Max: -70 db
Tracking force: 10 - 30 mN
Effective tonearm length:
9 in. (22.9 cm)
Overhang: .67 inch (17mm)
Platter diameter: 11.81 in. (30cm)
Platter weight: 4.5 lbs. (1.7kg)
Dimensions: 16.75 x 12.6 x 4.33 in. (415 x 230 x 110 mm)
Weight (including pkg.): 17lbs. (7.8 kg)

CARTRIDGE SPECIFICATIONS:

Frequency Response: 20Hz – 20kHz ± 3 dB
Channel Balance: 2dB @ 1kHz
Channel Separation: 20dB @ 1kHz
Sensitivity: 5mV ± 2 dB, 1kHz @ 5cm/sec
Static Compliance: 16mm/N
Equivalent tip mass: 0.7 mg
Vertical Tracking Angle: 26 degrees
Stylus Radius: Elliptical .0007" x .0003" (18 x 7)
Stylus Type: Replaceable
Load Resistance: 47,000 Ohm
Load Capacitance: 150 – 400pF
Internal Inductance: 560 mH
Internal Resistance: 700 Ohm
Cartridge Weight: 4.2g
Fixing Center: 0.5" (12.7mm)
Playing Weight 1.5 – 2.0g (1.75g nom.)

Music Hall reserves the right to make technical modifications.