RESPONSE D1

Rich open midrange, punchy bass, and large soundstage. Our new Mini Monitor.

Available in these real wood veneers











Speaker displayed in Ebony Finish.

Super AV Awards 2010 -Outstanding Overall Performance bookshelf speaker - Prestige Award



Super AV Awards 2010 ProAc Response D1



SPECIFICATIONS



8 ohms

20 to 100 watts Frequency Response

38Hz to 30kHz

87.5 db linear for 1 watt at 1 metre

Heavy, inert construction damped with special material and featuring slim, rigid front baffle design to aid dispersion.

New 5" (130mm) ProAc unit featuring glass fibre weave cone, raised spider assembly, EXCEL magnet system and unique acrylic damping phase plug.

ProAc 3/4 dome unit with honeycomb wound voice coil, special

Finest components on dedicated circuit board with multistrand oxygenfree copper cable throughout. Split for optional bi-wiring/biamping.

12" (305mm) high, 6 5/8" (168mm) wide, 10 1/4" (260mm) deep including grille thickness of 12mm

20lbs (9 Kgs)

Mode

Stand mounted

Acoustically transparent crimplene

Standard Finishes: Black Ash, Mahogany, Cherry, Maple. Premium Finishes: Rosewood, Ebony.

*Premium Finishes to





